

| | |
|--------------------------------------|--|
| Dimensions | 358 x 271.95 x 272.5 mm (14.1 x 10.7 x 10.7") |
| Weight | Without mount: 800 g (1.8 lb) With mount 980 g (2.2 lb) |
| Wind survivability | 200 km/h (125 mph) |
| Wind loading | 275 N at 200 km/h (61.8 lbf at 125 mph) |
| Hardware | |
| Networking interface | (1) GbE RJ45 port |
| Power method | Passive PoE 2-pair (4, 5+; 7, 8 return) |
| Power supply | 24V, 0.3A gigabit PoE adapter (Included) |
| Supported voltage range | 22–27V DC |
| Max. power consumption | 7W |
| Max. power output | 25 dBm |
| Gain | 23 dBi |
| Ambient operating temperature | -40 to 70° C (-40 to 158° F) |
| Ambient operating humidity | 5 to 95% noncondensing |
| Certifications | CE, FCC, IC |
| NDAA Compliant | Yes |
| Operating Frequency (MHz) | |

| | |
|------------------|---------------|
| Worldwide | 5150-5875 MHz |
|------------------|---------------|

| | |
|-----------------|---------------|
| USA | |
| U-NII-1 | 5150-5250 MHz |
| U-NII-2A | 5250-5350 MHz |
| U-NII-2C | 5240-5725 MHz |
| U-NII-3 | 5725-5850 MHz |

Management Radio (MHz)

| | |
|------------------|-----------------|
| Worldwide | 2412 - 2472 MHz |
|------------------|-----------------|

| | |
|--------------|-----------------|
| US/CA | 2412 - 2462 MHz |
|--------------|-----------------|