

## Hardware

<b>Dimensions</b>	294 x 31 x 80 mm (11.6 x 1.3 x 3.2")
<b>Weight</b>	400 g (14.1 oz)
<b>Enclosure material</b>	Outdoor UV-stabilized plastic
<b>Mounting</b>	Pole-mount (Kit included)

## Hardware

<b>Networking interface</b>	(2) 10/100 MbE RJ45 ports
<b>Power method</b>	Passive PoE 2-pair (4, 5+; 7, 8 return)
<b>Power supply</b>	24V, 0.5A PoE adapter (Included)
<b>Supported voltage range</b>	22–27V DC
<b>Max. power consumption</b>	8W
<b>Ambient operating temperature</b>	-30 to 75° C (-22 to 167° F)
<b>Operating Humidity</b>	5 to 95% noncondensing
<b>Shock &amp; vibration</b>	ETSI300-019-1.4
<b>Certifications</b>	FCC, ICC, CE, RoHS
<b>NDAA Compliant</b>	Yes

## System

<b>Frequency</b>	5 GHz
<b>Operating frequency</b>	
<b>Worldwide</b>	5170-5875 MHz
<b>USA</b>	5725-5850 MHz
<b>USA DFS</b>	5250-5850 Mhz
<b>Gain</b>	14.6-16.1 dBi
<b>Cross-pol isolation</b>	22 dB Min.
<b>Max. VSWR</b>	1.6:1
<b>Beamwidth</b>	43° (H-pol) / 41° (V-pol) / 15° (Elevation)
<b>Polarization</b>	Dual Linear