

^ Overview

Dimensions	Ø48.5 x 159.5 mm (Ø1.9 x 6.3")
WiFi Standard	WiFi 6
Spatial Streams	6
Coverage Area	140 m ² (1,500 ft ²)
Max. Client Count	250+
Uplink	GbE
Mounting	Wall, Pole (Mounts Included)
Weatherproofing	IPX5
Power Method	PoE

^ Performance

MIMO

5 GHz 4 x 4 (DL/UL MU-MIMO)

2.4 GHz 2 x 2 (DL/UL MU-MIMO)

Max. Data Rate

5 GHz 4.8 Gbps (BW160)

2.4 GHz 573.5 Mbps (BW40)

Antenna Gain

5 GHz 5 dBi

2.4 GHz	3 dBi
Max. TX Power	
5 GHz	26 dBm
2.4 GHz	22 dBm
Max. BSSIDs	8 per Radio
Supported Data Rates	
802.11ax (WiFi 6)	7.3 Mbps to 4.8 Gbps (MCS0 - MCS11 NSS1/2/3/4, HE 20/40/80/160)
802.11ac (WiFi 5)	6.5 Mbps to 3.4 Gbps (MCS0 - MCS9 NSS1/2/3/4, VHT 20/40/80/160)
802.11n	6.5 Mbps to 600 Mbps (MCS0 - MCS31, HT 20/40)

^ Features

Wireless Meshing	✓
Band Steering	✓
802.11v BSS Transition Management	✓
802.11r Fast Roaming	✓
802.11k Radio Resource Management (RRM)	✓
Advanced Radio Management	✓
Passpoint (Hotspot 2.0)	✓
Captive Hotspot Portal	
Custom Branding Landing Page	✓
Voucher Authentication	✓
Payment-Based Authentication	✓
External Portal Server Support	✓
Password Authentication	✓
Guest Network Isolation	✓
Private Pre-Shared Key (PPSK)	✓
WiFi Speed Limiting	✓
Client Device Isolation	✓

WiFi Schedules	✓
RADIUS over TLS (RadSec)	✓
Dynamic RADIUS-assigned VLAN	✓
^ Hardware	
Max. Power Consumption	13W
Includes PoE Adapter	✓
Supported Voltage Range	44—57V DC
Networking Interface	(1) GbE RJ45 port
Weight	400 g (14.1 oz)
Management	Ethernet
Enclosure Material	Polycarbonate, aluminum
Mount Material	Polycarbonate
LEDs	
System	White/Blue
Channel Bandwidth	HT 20/40, VHT 20/40/80/160, HE 20/40/80/160 (MHz)
NDAA Compliant	✓
Certifications	CE, FCC, IC, SRRC, Anatel: 02111-22-08356
Operating Frequency	US/CA: 2400 - 2472 MHz U-NII-1: 5150 - 5250 MHz U-NII-2A: 5250 - 5350 MHz U-NII-2C: 5470 - 5725 MHz U-NII-3: 5725 - 5850 MHz Worldwide: 2400 - 2483.5 MHz 5150 - 5725 MHz
Ambient Operating Temperature	-30 to 60° C (-22 to 140° F)
Ambient Operating Humidity	5 to 95% noncondensing
^ Software	
Application Requirements	
UniFi Network	Version 6.0.45 and later