

## Mechanical

<b>Dimensions</b>	452.3 x 78.7 x 54.4 mm (17.8 x 3.1 x 2.14")
<b>Weight</b>	420 g (14.82 oz)
<b>Wind survivability</b>	200 km/h (125 mph)
<b>Wind loading</b>	77 N at 200 km/h (17.3 lbf at 125 mph)

## Hardware

<b>Networking interface</b>	(1) GbE RJ45 port
<b>Power method</b>	Passive PoE 2-pair (4, 5+; 7, 8 return)
<b>Power supply</b>	24V, 0.5A gigabit PoE adapter (Included)
<b>Supported voltage range</b>	20—27V DC
<b>Max. power consumption</b>	8W
<b>Antenna gain</b>	16 dBi
<b>ESD/EMP protection</b>	Air/contact $\pm$ 24kV
<b>Shock and vibrations</b>	ETSI300-019-1.4
<b>Ambient operating temperature</b>	-40 to 70° C (-40 to 158° F)
<b>Ambient operating humidity</b>	5 to 95% noncondensing
<b>Certifications</b>	CE, FCC, IC

## Operating Frequency (MHz)

<b>US/CA</b>	
<b>U-NII-1</b>	5150 - 5250 MHz
<b>U-NII-2A</b>	5250 - 5350 MHz
<b>U-NII-2C</b>	5470 - 5725 MHz
<b>U-NII-3</b>	5725 - 5850 MHz
<b>Worldwide</b>	5150 - 5875 MHz
<b>NDAA Compliant</b>	Yes